

DB18

The King plant drawbars come with the same features as the UK's most popular stepframe trailer.



With drawbar operations, much more attention is required to distribute the load and with King's extensive experience of trailer build can help you ensure that those loads you wish to carry are possible.

KEY FEATURES

DECK

6.10m long x 2.55m wide covered in 29mm hardwood. Laden height 896mm nominal. 4 off 2.25t shackles to main deck. Ropehooks as standard. Fitted with 50mm towing eye. Towing height set at 650mm high. Single front leg fitted.

BEAVERTAIL

1.42m long x 2.55m wide covered in 29mm hardwood. Beavertail angle 9°. 2 off 2.25t shackles to beavertail. Ropehooks as standard.

RAMPS

2.5m long x 1.00m wide hydraulic ramps off the beavertail are standard fitment, all steel construction covered in 29mm hardwood.

AXLES/SUSPENSION

2 x 9 tonne (design) axles with air suspension and raise/lower facility. Electronic roll stability fitted as standard.

WHEELS & TYRES

235/75R 17.5 low profile tyres fitted to U17.5 x 6.75R -10 stud steel spigot disc wheels - 8 off supplied. Primer and two pack single colour top coat of customers choice.



DURABLE



VERSATILE



WELL PROVEN DESIGN



SAFE EFFICIENT OPERATION



MAXIMUM PAYLOAD

BRAKES/ELECTRICS

2 line air operated 'S' cam type drum brakes complete with load sensing and EBS. 'C' type air couplings, spring brakes fitted. 24 volt ISO standard system wired via two 7 pin and one 15 pin plug.

FINISH

All steel parts shot blasted to SA2.5 followed by high build primer and two pack single colour top coat of customers choice.