



Group of Companies

KING TRAILERS LIMITED

Riverside, Market Harborough,  
Leicestershire, LE16 7PX

Telephone: +44 (0) 1858 467361

Fax: +44 (0) 1858 467161

info@kingtrailers.co.uk

[www.king.uk.com](http://www.king.uk.com)

## DBP12/2-17.5 – Close Coupled Plant Drawbar Trailer

06.07.16



### Key features

**Main deck** – 6.10m long x 2.55m wide covered in 29mm hardwood. Laden height t896mm nominal. 4 off 2.25t shackles to main deck. Ropehooks as standard.

**Beavertail** – 1.42m long x 2.55m wide covered in 29mm hardwood. Beavertail angle 9°. 2 off 2.25t shackles to beavertail. Ropehooks as standard.

**Axles and suspension** – 9 tonne axles fitted with fully equalising air suspension complete with raise/lower facility.

**Wheels and tyres** – 235/75R 17.5 low profile tyres fitted to U17.5 x 6.75R -10 stud steel spigot disc wheels – 8 off supplied.

**Brakes and electrics** – 2 line air operated ‘S’ cam type drum brakes complete with load sensing and EBS. ‘C’ type air couplings, spring brakes fitted. 24 volt ISO standard system wired via two 7 pin plugs.

**Rear ramps** – 2.5m long x 1m wide hydraulic off beavertail. All steel construction overlaid with 29mm hardwood. Drop down legs at rear of beavertail for stability when loading (PTO operated – option power packs available).

**Finish** – All steel parts shot blasted to SA2.5 followed by high build primer and two pack single colour top coat of customer’s choice.

**Draw beam** – Fitted with 50mm towing eye. Towing height set at 650mm high. Single front leg fitted.

Plating Data	Design	C&U
Gross trailer weight	12,000kg	12,000kg
Axle capacity	6,000kg	6,000kg
Approx. tare weight	5,000kg	5,000kg
Payload (approx.)	7,000kg	7,000kg

\*Tare weight and payload vary depending on options supplied.

KING VEHICLE ENGINEERING LIMITED AND ASSOCIATED COMPANIES

Riverside, Market Harborough, Leicestershire, England, LE16 79X. Telephone: +44 (0) 1858 467361. Fax: +44 (0) 1858 467161. [www.king.uk.com](http://www.king.uk.com)  
Due to the policy of continuous improvement, King reserves the right to amend specifications without notice.