

Variosign 3 x 3 Specification

13.12.16

- Size 1390 x 1390 mm
- Display luminance level automatic
- LED pitch 20mm
- Housing material aluminium, seawater resistant
- Housing rating IP 56
- Lighting Protection Unit (LPU)
- Ambient temperature range -40 - +50
- Sign setting PC / laptop based software with internet connection
- Sign display capable of setting signs individually or as a group
- Cable remote control
- Power source mains, 230 AC, 12V / 24V DC
- EN12966, CE approved

ROTTMS KEY FEATURES

- Wickets up to 5 lanes with relevant variants (1 mile, 800 yards, 600 yards, 400 yards or 200 yards)
- All displays as per the DfT Signs Authorisation
- LED display colour red and white
- Sign lifting eyes equipped as standard
- Display sequence displays automatically the corresponding distance for TSRGD diagram 572 or 7202.1
- Security software prevents conflicting aspects being displayed in the same group of signs
- Capable of sending and receiving control messages
- Capable of sending and receiving status replies
- Automatic fault reporting
- Automatic logging of data (user, time, display messages, etc.)
- Equipped with bulkhead mounted mains inlet and comms connector
- Approvals – EN12966, CE approved, Highways Agency type approved, TOPAS approved, TR2603 compliant, signs authorisation by DfT, code of connection in accordance with MCH1514, EMC as per BS EN 50293