

Variable Messaging Trailer





Group of Companies

Variable Messaging Trailer



LED matrix board is capable of displaying any static or dynamic Variable Messaging signs (VMS), text or symbols.

Matrix board is available with red, amber, white and blue LEDs.

Highly legible signs even in bright daylight Available as partially or fully populated versions.

Simple handset control of matrix board.

Optional remote control and monitoring.

All signs stored on a "memory stick" which can be easily be re-programmed.

Remote activation and sign creation available as an option.

Housing

Aluminium, water resistant seal (ALMG3), black power coated

Approx. 145kgs

Weight

Size of housing

2190 x 1590 x 130mm

Size of LED area

1680 x 1200mm

LED/m² Matrix

4444

No. of LEDs

8960 per colour

Light Source

15°, LED red, amber, white 5mm

LED Pitch

15mm

Matrix Brightness

Amber/red: 20,000 cd /m²

Voltage

12/24 V Nominal

Auto Brightness

Continuous 5% - 100% also manually adjustable

Adaption

Data Storage

250 symbols per memory stick



KING VEHICLE ENGINEERING LIMITED AND ASSOCIATED COMPANIES

KING TRAILERS LIMITED | KING HIGHWAY PRODUCTS LIMITED | KING TRANSPORT EQUIPMENT LIMITED | SAFETY VEHICLE HIRE AND LEASE LIMITED

Riverside, Market Harborough, Leicestershire, England, LE16 79X. Telephone: +44 (0) 1858 467361. Fax: +44 (0) 1858 467161. www.king.uk.com
Due to the policy of continuous improvement, King reserves the right to amend specifications without notice.